

Record the results of a test as CSV from the REALM monitor script

Goal: Record the results of a LANforge test as a CSV file.

Some scripts in the LANforge library have a monitor function built in.

We are going to be using the `test_ipv4_variable_time` script for this demonstration.

This is useful for running a test and then analyzing the results afterwards.

-
1. Start LANforge GUI. It is recommended to run this script on a fresh LANforge configuration with no stations loaded.
 2. Make sure you have lanforge-scripts on your device.
If lanforge-scripts is already installed on your device, skip this step
Navigate to py-scripts in the lanforge-scripts folder. If your LANforge device doesn't have this open source software yet you can clone them from [Github](#)
To install lanforge-scripts paste `git clone https://github.com/greearb/lanforge-scripts` into your terminal.
 3. Type the following command into your command line
`./test_ipv4_variable_time.py --radio wiphy0 --security wpa2 --ssid lanforge --password password --output_format csv`
Replace the security, ssid, and password variables with the settings for the network you are testing.
This will create 2 wiphy stations by default, connect them to the network you are testing, and report the results to a CSV file. You can change the following fields in the Realm Monitor function:
 4. This creates a default file in your report-data folder under your home directory. The name will be in the format with today's timestamp and the name of the test you ran. It's a normal Excel file which you can use however you want..
 5. There are multiple commands you can use with this function, here is a list of the flag and what each of them mean:
 - A. `report_file`: Name the full path of the file you want to save results to. Default will save to your report-data folder.
 - B. `duration_sec`: how long you want to run the test

- C. output_format: The output format you want your file in. The following formats are supported:
- A. xlsx DEFAULT
 - B. pickle
HINT: pickle is recommended if you are going to be manipulating data in python since it preserves formatting and can be quickly loaded into a Pandas DataFrame without any manipulation required
 - C. csv
 - D. json
 - E. pdf
WARNING: PDF is hard to export data from without an Adobe Acrobat license
 - F. png
WARNING: png is going to export an image, do not use this if you are planning on manipulating your data because it does not preserve the numbers recorded
 - G. html
 - H. hdf
 - I. parquet
 - J. stata
- D. ssid: REQUIRED Name of the network you are connecting to
- E. password: REQUIRED Password to the network
- F. radio: REQUIRED The radio which you are going to create stations from.
- G. security: Match the security protocol of your router.
- H. test_duration: Default is 60 seconds, write in a any number if you need. You can also use minutes or hours notation in this command, so for 42 minutes write 42m and for 8 hours write 8h.
- I. upstream_port: Most users won't need to use this option, but it tells the program where to connect to the router
- J. created_cx: List of the cross connects you are going to be analyzing. If you are starting with no stations created, you won't need to use this option.